

Technical Datasheet

SUPER CAT Bonding Primer

Product Description: Water-based white acrylic primer for interior and exterior walls intended to fix the surface and improve its bonding with acrylic paints and plasters. Penetrates the surface and strengthens it. Reduces the absorption of the surface, which enables obtaining a more homogeneous topcoat with a better spread rate.

Typical Uses: Serves as a first coat on black plaster or concrete before application of acrylic wall paints such as Nirocryl Extra, Nirocryl 2000, Nirocryl 100, Nirocryl Satin or decorative coatings such as Super Flexible or Tulip Plaster.

Surface Preparation: Clean new black plaster with a broom and rinse with water to remove loose grains of plaster. On existing walls remove all peeling or loose paint and ensure that the remaining paint is firmly attached to the walls. Repair defects and holes and smooth with Maximo Crack Filler or Altek Violet (with addition of 25% cement). Open cracks and, after primer is applied, fill with Niroseal or Flexible Wall Putty. Wash painted walls with a water pressure machine to remove soot, dust and dirt.

Application: Roller, brush or sprayer. Use a brush in corners where the roller cannot reach. Do not apply the material when the temperature is below 7 °C or when rain is predicted.

Dilution: 20%-100% water.

Colour: White, can be tinted in pastel shades.

Gloss level: Matt.

Coverage: 3.5-4 m²/L on black plaster and 5-7 m²/L on spackle plaster.

*The coverage capability is calculated according to the work of a skilled laborer on a surface with an ordinary degree of absorption and may vary according to the working method and weather conditions.

Cleaning: Clean tools and hands with water immediately after use.



mail: info@pycatpaints.com
tel: 7001203
web: www.pycatpaints.com

Technical Datasheet

Dry Time:

To touch: 4-6 hours

To recoat: 4-6 hours

Complete drying: 24 hours.

Shelf life and Storage: 18 months, in a closed bucket, in a cool and dry place.

Packaging: 1,3,9 and 18 L.

VOC (Volatile Organic Compounds):

EU limit value for this product (Cat. A/a): 75 g/l (2007) and 30 gr/l (2010). This product contains max 6.8 g/l.

Manufactured by: Nirlat Ltd, Kibbutz Nir-Oz, DN Negev 85122, Israel, www.nirlat.com

Health and Safety precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat.

General Notes: The aforementioned recommendations are not to be perceived as substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.



70001203

mail:info@pycatpaints.com
tel:7001203
web:www.pycatpaints.com